

GV-PCR310 Enrollment Reader



The GV-PCR310 is a USB card reader designed to assist with card enrollment to GV-ASManager. It reads and transfers the identification data of a detected card to GV-ASManager. The user can conveniently establish user accounts on GV-ASManager by inserting the cards at the GV-PCR310 Enrollment Reader.

SPECIFICATIONS

System Requirements		
OS	32-bit	Windows XP / Vista / 7 / 8 / Server 2008
	64-bit	Windows 7 / 8 / Server 2008 R2 / Server 2012
GV-ASManager Version	V4.1 or later	
Operational		
Frequency	13.56 MHz, ISO14443A Mifare Classic	
Distance	2 cm	
Environmental		
Operating Temperature	-10 ~ 60° C (14 ~ 140° F)	
Operating Humidity	10 ~ 90% RH (non-condensing)	
Mechanical		
LED Indicator	2 LED (power, status)	
Connector	USB	
Dimensions	65 x 100 x 24.7 mm (2.6" x 3.9" x 0.97")	
Cable Length	160 cm (63")	
Weight	115 g (0.25 lb)	
Others		
Certification	CE, FCC	

[Installation Guide](#)

Note: Specifications are subject to change without notice.

Options

GV-AS ID Card & GV-AS ID Key Fob	GV-AS ID Cards and GV-AS ID Key Fobs are ideal for business and residential environment, where access control is important for security reasons. The 13.56 MHz cards and key fobs are available.
GV-AS ID F Card & GV-AS ID F Key Fob	