

GV-BX4700 Series 4MP H.265 Super Low Lux WDR Pro D/N Box IP Camera

GV-BX4700-8F



GV-BX4700-3V



- 1/2.7" progressive scan super low lux CMOS
 - Min. illumination at 0.02 lux
 - Dual streams from H.265, H.264 and MJPEG
 - Up to 25 fps at 2560 x 1440, 30 fps at 2048 x 1520
 - P-Iris for auto iris adjustment
 - Built-in / external microphone
 - 2-way audio
 - One sensor input and alarm output
 - TV-out support
 - Built-in micro SD card slot for local storage
 - Recording assigned by GV-Edge Recording Manager (Windows, Mac version)
 - Mini USB slot for WiFi adapter or USB hard drive
 - Wide Dynamic Range Pro (WDR Pro)
 - 3D noise reduction
 - Smart streaming
 - Defog
 - Privacy mask
 - IP address filtering
 - 12V DC / PoE (IEEE 802.3af)
 - Removable IR-cut filter for Day/Night function
 - Varifocal megapixel lens
 - Supports iPhone, iPad, Android & 3GPP
 - 31 languages on Web interface
 - ONVIF (Profile S) conformant
- * No Memory card slot & local storage function for Argentina.
* Smart streaming requires either GV-DVR / NVR V8.7.0.0 or GV-VMS V16.10.0.0.

Introduction

The GV-BX4700 is a series of indoor IP cameras containing a varifocal and a fixed focal model. GV-BX4700 can support H.265 video codec to achieve better compression ratio while maintaining high picture quality at reduced network bandwidths. The camera is equipped with a Super Low Lux CMOS image sensor which allows the camera to provide a color live view in near darkness. The camera features a mini USB port which supports wireless connection through a GV-WiFi Adapter (optional) or external storage using a USB hard drive.

Models


Models	Iris	Focal Length (mm)	Maximum Aperture	Image Format
GV-BX4700-3V	P-Iris	3 ~ 10.5 mm	F/1.4	1/2.7"
GV-BX4700-8F	Fixed	2.8 mm	F/1.8	1/2.7"

Active Tampering Alarm


Tampered




Focus Change



Camera Shift



Dimensions



Model	L Length
BX4700-3V	35.38 mm (1.39")
BX4700-8F	15.7 mm (0.62")

Specifications

Camera	GV-BX4700-8F	GV-BX4700-3V
Image Sensor	1/2.7" progressive scan super low lux CMOS	
Picture Elements	2560 (H) x 1440 (V)	
Minimum Illumination	Color	0.03 Lux
	B/W	0.02 Lux
	IR ON	0 Lux
Shutter Speed	Automatic, Manual (1/5 ~ 1/6000 sec)	
White Balance	Automatic, Manual (2800 ~ 8500K)	
Gain Control	Automatic	
S/N Ratio	50 dB	
WDR Pro	Yes	
Dynamic Range	100 dB	
Lens		
Megapixel	Yes	
Day/Night	Yes (with removable IR-cut filter)	
Lens Type	Fixed	Varifocal
Focal Length	2.8 mm	3 ~ 10.5 mm
Maximum Aperture	F/1.8	F/1.4
Mount	CS Mount	
Image Format	1/2.7"	
Horizontal FOV	104°	78° ~ 31°
Operation	Focus	Manual (w/lock)
	Zoom	Fixed
	Iris	N/A
Torque (Focus/Zoom screws)	0.049 N.m	
Operation		
Video Compression	H.265, H.264, MJPEG	
Video Streaming	Stream 1 from H.265 or H.264 Stream 2 from H.265, H.264 or MJPEG	
Frame Rate	50Hz: 25 fps at 2560 x 1440, 25 fps at 2048 x 1520 60Hz: 24 fps at 2560 x 1440, 30 fps at 2048 x 1520 * The frame rate and performance may vary depending on the number of connections and data bitrates (different scenes).	
Image Setting	Brightness, Contrast, Saturation, Sharpness, Gamma, White Balance, Flicker-less, Image Orientation, Shutter Speed, Backlight Compensation, D/N Sensitivity, WDR, Defog, Low Lux Enhancement, Denoise, Metering	
Audio Compression	G.711	
Audio Support	Two-way audio	
Sensor Input	1 input (dry contact)	
Alarm Output	1 digital output (200 mA 5V DC)	
Video Resolution		
Main Stream	4:3	2048 x 1520, 1600 x 1200, 1280 x 960, 640 x 480,
	16:9	2560 x 1440 (default), 2304 x 1296, 1920 x 1080, 1280 x 720, 640 x 360
	5:4	1280 x 1024, 640 x 512
Sub Stream	4:3	1024 x 768, 640 x 480, 320 x 240

	16:9	1280 x 720, 640 x 360 (default), 448 x 256	
	5:4	1280 x 1024, 640 x 512, 320 x 256	
Network			
Interface		10/100 Ethernet	
Protocol		DHCP, DynDNS, FTP, HTTP, HTTPS, NTP, ONVIF (Profile S), PSIA, QoS (DSCP), RTSP, SNMP, SMTP, TCP, UDP, UPnP, 3GPP/ISMA	
Wireless LAN		IEEE 802.11 b/g/n	
Antenna Type		External	
Security		WEP, WPA-PSK(TKIP), WPA-PSK(AES), WPA2-PSK(TKIP), WPA2-PSK(AES)	
Mechanical			
Temperature Detector		Yes	
Connectors	Power	2-pin terminal block, PoE	
	Ethernet	Ethernet (10/100 Base-T), RJ-45 cable	
	Audio	1 In (built-in or external microphone) 1 Out (stereo phone jack, 3.5 mm / 0.14")	
	Digital I/O	3-pin terminal block, pitch 2.5 mm (0.1")	
	Auto Iris	Yes (with varifocal lens)	
	Local Storage	Micro SD card slot (SD/SDHC/SDXC/UHS-I, Class 10) *UHS-II card type is not supported.	
	TV-Out	BNC connector (640 x 480 resolution)	
	Mini USB	GV-WiFi Adapter or USB hard drive	
LED Indicator		2 LEDs: Power, Status	
General			
Environment Temperature	Start-up	0 °C ~ 50 °C (32 °F ~ 122 °F)	
	Operation		
Humidity		10% to 90% (no condensation)	
Power Source		12V DC / PoE (IEEE 802.3af)	
Max. Power Consumption		12V DC, 4.23W	
Dimensions (without lens)		75.5 x 75 x 54 mm (2.97" x 2.95" x 2.13")	
Weight		320 g (0.7 lb)	350 g (0.77 lb)
Regulatory		CE, FCC, RCM, LVD, RoHS compliant	
Power over Ethernet			
PoE Standard		PoE (IEEE 802.3af Power over Ethernet / PD)	
PoE Power Supply Type		End-Span, Mid-Span	
PoE Power Output		Per Port 48V DC, 350 mA, Max. 15.4 watts	
Web Interface			
Installation Management		Web-based configuration	
Maintenance		Firmware upgrade through Web Browser or Utility	
Access from Web Browser		Camera Live View, Video Recording, Change Video Quality, Bandwidth Control, Image Snapshot, Audio, Picture in Picture, Picture and Picture, Privacy Mask, Text Overlay, Digital PTZ	
Language		Arabic / Bulgarian / Czech / Danish / Dutch / English / Finnish / French / German / Greek / Hebrew / Hungarian / Indonesian / Italian / Japanese / Lithuanian / Norwegian / Persian / Polish / Portuguese / Romanian / Russian / Serbian / Simplified Chinese / Slovakian / Slovenian / Spanish / Swedish / Thai / Traditional Chinese / Turkish	
Applications			
Network Storage		GV-Backup Center, GV-VMS	
Smart Device Access		GV-Eye for iOS and Android	
Live Viewing		IE, Mobile App	
CMS Server support		GV-Control Center, GV-Center V2, GV-Vital Sign Monitor	

Note:





- The signal range and data throughput may vary depending on the network conditions and environmental factors.
- Mind the following limitations and requirements for the mini USB port:
 - The USB hard drive must be of 2.5" or 3.5", version 2.0 or above
 - The USB hard drive's storage capacity must not exceed 2TB
 - USB flash drives and USB hubs are not supported
 - External power supply is required for the USB hard drive
 - To connect a GV-WiFi Adapter, make sure it is connected before the camera is powered on.
- Specifications are subject to change without notice.
- Mind the following when using a memory card for recording:





- Recorded data on the memory card can be damaged or lost if the data are accessed while the camera is under physical shock, power interruption, memory card detachment or when the memory card reaches the end of its lifespan. No guarantee is provided for such causes.
 - The stored data can be lost if the memory card is not accessed for a long period of time. Back up your data periodically if you seldom access the memory card.
 - Memory cards are expendable and their durability varies according to the conditions of the installed site and how they are used. Back up your data regularly and replace the memory card annually.
 - To avoid power outage, it is highly suggested to apply a battery backup (UPS).
 - For better performance, it is highly suggested to use Micro SD card of MLC NAND flash, Class 10.
 - Replace the memory card when its read/write speed is lower than 6 MB/s or when the memory card is frequently undetected by the camera.
5. To use the GV-Eye application, change the video codec setting to H.264 for the GV-IP CAM H.265 models.

Packing List

- | | |
|--|--------------------------|
| 1. H.265 Box Camera | 6. Camera Holder |
| 2. Terminal Block (2-Pin and 3-Pin) | 7. Holder Screw x 2 |
| 3. Fixed Focal or Varifocal Megapixel Lens | 8. GV-IPCAM Software DVD |
| 4. Six Lens Rings | 9. GV-Software DVD |
| 5. Video Out Wire | 10. Warranty Card |

Accessories

Model No.	Name	Details
GV-Mount300	Convex Corner Adapter Kit	Dimensions: 238.6 x 409.5 mm (9.4" x 16.1") Weight: 4.27 kg (9.41 lb)
		
GV-Mount310	Concave Corner Adapter Kit	Dimensions: 123.3 x 393.1 mm (4.9" x 15.5") Weight: 2.96 kg (6.53 lb)
		
GV-Mount400	Pole Mount Bracket Kit (Ø 4" ~ 6")	Dimensions Bracket: 241 x 161 mm (9.5" x 6.3") Weight: 1.70 kg (3.75 lb) Steel Strap Diameter: Ø 4" ~ 6"
		
GV-Mount410	Pole Mount Bracket Kit (Ø 6" ~ 7.5")	Dimensions Bracket: 241 x 161 mm (9.5" x 6.3") Weight: 1.70 kg (3.75 lb) Steel Strap Diameter: Ø 6" ~ 7.5"
		

Model No.	Name	Details
GV-Housing102	Housing Box (with heater and fan)	<p>Dimensions: 406 x 145 x 109 mm (16 x 5.7 x 4.3")</p> <p>Weight: 4.69 kg (10.34 lbs) (including Supporting Tube)</p> <p>Start-up Temperature: -30°C ~ 50°C (-22°F ~ 122°F)</p> <p>Operation Temperature: -40°C ~ 50°C (-40°F ~ 122°F)</p> <p>Heater: 15°C (59°F) On / 25°C (77°F) Off</p> <p>Fan: 35°C (95°F) On / 25°C (77°F) Off</p> <p>Power board: 24V AC or 12V DC input</p>
IP67	IK10	
GV-PA191 PoE Adapter		<p>Weight: 130 g / 0.29 lb</p> <p>Dimensions (H x W x D): 43 x 69 x 40 mm / 1.69 x 2.72 x 1.57 in</p>
GV-WiFi Adaptor		<p>Weight: 20 g / 0.04 lb</p> <p>Dimensions (H x W x D): 15 x 15 x 155 (mm) / 0.59 x 0.59 x 6.10 (in)</p> <p>Supplied with mini USB to standard USB adapter.</p>
GV-Relay V2		<p>The GV-Relay V2 is designed to expand the voltage load of GV IP devices. It provides 4 relay outputs, and each can be set as normally open (NO) or normally closed (NC) independently as per your requirement.</p>
Power Adapter		<p>Contact your sales representative for the countries and areas supported.</p>
GV-POE Switch		<p>The GV-POE Switch is designed to provide power along with network connection for IP devices. The GV-POE Switch is available in various models with different numbers and types of ports.</p>